

IMT-SA110-6 SURFACE MOUNT ADHESIVE

IMT-SA110-6 is a single component, surface mount epoxy adhesive formulated to bond chips or components onto printed circuit boards. This SMT adhesive was designed to screen print using metal blade and possesses a wide curing window. IMT-SA110-6 offers excellent heat, chemical resistance and exhibits exceptional adhesion strength on PC boards.

IMT-SA110-6 is solventless, 100% solid system and does not contain hazardous and/or prohibited substances. It complies to RoHS3, EU directive 2015/863, Substances of Very High Concern (SVHC) published by ECHA as well as Halogen Free.

TYPICAL PROPERTIES*

Cure Conditions	1. 150°C for 60s 2. 130°C for 5mins 3. 120°C for 10mins
-----------------	---

Physical Properties

Color	Red before and after cure
Consistency	Thixotropic paste
Specific Gravity	1.44
Viscosity @10rpm, 25°C	20,000cPs
TI Index (1/10rpm), 25°C	3.35
Solid Content	100%
Glass transition temperature	> 130°C
Shore D Hardness	90
Die Shear Strength	> 15Kgf per 3.5 x 2mm die on FR4 substrate
Volume Resistivity	> 1 x 10**14Ωcm
Operating Temperature	-40°C to above 150°C

Ionic Contents

Chloride, Cl-	≤ 650ppm
Bromine, Br-	Not detected
PVC	Not detected

Pot Life	2 weeks at room temperature
Shelf Life	12 months at -20°C or below

IN-MAT TECHNOLOGIES (S) PTE LTD
623 ALJUNIED ROAD, #05-09, ALJUNIED INDUSTRIAL COMPLEX
SINGAPORE 389835
Tel / Whatsapp / Wechat: +65 8688 8711
E-Mail: sales@inmat-tech.com
Website: www.inmat-tech.com

* The information is based on data and tests believed to be accurate. In-Mat Technologies (S) Pte Ltd makes no warranties as to its accuracy and assumes no liability in connection with the use or inability to use this product.